Pro9542dn Specifications





OKI takes graphic arts printing to a new level with the Pro9542dn, offering outstanding print quality, higher print speeds, lower total cost of ownership, complete media flexibility plus the unique option of printing with a fifth colour. You can now print on-demand, the full range of process colours, including solid white on a dark background.

Plus, the Pro9542dn is also fully compatible with EFI Fiery XF 5.0 server which enables advanced colour management, including white and process colours, optimising colour depth and print quality.

A first in digital LED printing - CMYK + White

The Pro9542dn is an affordable and unique high definition printer that enables you to not only print the full range of process colours but also offers white.

- Print in a full range of process CMYK colours
- Plus now add a spot colour white for printing on darker media
- Stunning vibrancy of colour on dark or transparent media

Stunning high definition colour

The Pro9542dn uses the combination of digital LED technology and our Multi-Level ProQ technology to produce the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output
- Fully compatible with EFI Fiery® XF for advanced colour management

Low total cost of ownership

The Pro9542dn combines a highly competitive capital cost and ultra-high capacity toners cartridges to deliver a considerably reduced total cost of ownership, essential where high coverage and quality is demanded.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges and drums
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage

Speed that you can rely upon

Offering the highest printing speeds on the market, the Pro9542dn delivers faster short run on-demand printing.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)
- 2GB RAM and 1.2GHz processor for rapid throughput

Media flexibility to beat all others

Beating the competition hands down when it comes to media flexibility, the Pro9542dn enables you to print in-house on a complete range of media.

- Widest paper handling from A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Duplex printing as standard
- Prints on a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility

A3/A4	~
Colour/Mono	~
Prints A6 to 1321mm, up to 360gsm	~
White spot colour for printing on darker media	~
1 - 30+ users	



Pro9542dn - Colour and Mono Printer

Printer		OPERATOR PANEL	
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono. White: up to 45ppm (simplex) Clear: 18ppm	LCD Display	10.9cm Colour Graphic LCD (480x272 dots)
Time to first print	8 seconds colour, 8 seconds mono	GENERAL FEATURES	
Warm up time	50 seconds or less from power on	Memory	Standard RAM: 2GB; Maximum RAM: 2GB
Processor speed	1.2GHz	Memory	Optional Hard Disk Drive: 160GB
INTERFACE AND SOFTWARE		Environment	Operating temperature/humidity: 10°C to 35°C (17°C to 27°C recommended) / 10% to 85% RH (50% to 70% RH recommended)
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T		Storage temperature/humidity: -10°C to 43°C, 10% to 90%RH
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF Printing (v1.7), XPS, SIDM	Power supply Power consumption	Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz Typical: 1200W; Max: 1500W; Idle: 200W (average);
	DDNS, UPnR, Bonjour, WINS, SSL/TLS, SMTP, SMTP over SSL, POP3, SNTP, JCDP, FLDP, ODNSP, WSDPrint, WSD-Discovery, Web JetAdmin, NetBIOS over TCP, EtherTalk	Noise level	Power Save: <26W; Deep Sleep: <4W; Off Mode: <0.5W Operating: 57dB(A);
		Dimensions (HxWxD)	Standby: 32dB(A) or less; Power save: Inaudible
Network & protocols			640 x 699 x 625mm
		Weight ⁴	110.8kg
		Duty Cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month
OS Compatibility ¹	Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Windows 7 (32-bit & 64-bit) / Server 2012	Warranty	1 year pan europen warranty
, ,	(64-bit) / Windows 8 (32-bit & 64-bit); Mac OS9 / OS X 10.3.9	Product order number	Pro9542dn: 45530622
	- 10.9	Accessories (Order Numbers)	
	Irity Sec, EAP-PEAP, EAP-TLS, Secure Erase ³ , Secure Print ³ , Secure Print Job Encryption ³ , Storage Devices entire Encryption ³ ,	2nd/3rd paper tray	45530703
Advanced networking and security		2nd/3rd paper tray 2nd/3rd paper tray with castor	45530903
		High Capacity Feeder	45530803
	Storage(HDD) Initialize (format) ³	Hard Disk Drive	
	Print Job Accounting ² , Print Job Accounting Enterprise ² , Print Job Accounting Client, PrintSuperVision.net ² , Template Manager ² ,	EFI Fiery XF 5.0	Contact Oki for more information
Utility suite ¹	Color Correct, Color Swatch ² , Configuration Tool, PS Gamma Adjuster, Profile Assistant (Mac Only), PDF Direct Print, EFI Fiery		45980001
		CONSUMABLES (ORDER NUMBERS)	
	XF Server Option (External color management server)	Toner cartridge* Cyan, 45536555, Maganta, 45536554	
Typefaces		(42,000 pages) Toner Cartridge*	
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bitmap fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts	(24,000 pages) Toner Cartridge*	Yellow: 45536437
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes	(51,000 pages)	Black: 45536556
		Toner Cartridge (15,000 pages)	White: 45536543
PRINT QUALITY	D 0/000 M IV I I I I I I I I I I I I I I I I I	Image drums** (40,000 pages)	Cyan: 45103721; Magenta: 45103720; Yellow: 45103719; Black: 45103722
Resolution Enhancements	ProQ4800 Multi-level technology, 1200 x 1200dpi Auto Colour Balance, Auto Registration, Auto Media Detect	Image drum** (20,000 pages)	White: 45103765
PAPER HANDLING		Transfer Belt (150,000 pages)	45531223
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets of 80gsm	Fuser Unit (150,000 pages)	45531113
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm	Waste Toner Box (40,000 pages)	45531503
Maximum paper capacity	2,950 sheets of 80gsm		ISO coverage. Printer shipped with toner for 24,000 pages CMY
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6; Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B4, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), SRA4, A4, A5, A6, B4, B5, B6	and 38,000 pages K @ ISO. **Drum: Average number of A4 pages printed.	
	Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm;		
Paper weight	Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm		
Paper weight Duplex	Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm Standard		

 $^1 Check\ local\ OKI\ website\ for\ latest\ driver\ releases\ and\ OS\ compatibility;\ ^2 Windows\ only;\ ^3 HDD\ required;\ ^4 Including\ all\ consumables;$

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI SYSTEMS (POLSKA) Sp. z o.o.

42 Domaniewska str. Warsaw 02-672 Poland

T +48(0) 22 44 86 500 F +48(0) 22 44 86 501

WWW.OKIEUROPE.COM



